

Blood Collection Monitor

Features:

- Unique modern sensor and LED display.
- Preset volume of blood collection function.
- Taring and calibrating function, ensure measuring accuracy.
- Soft shaking mode, improving the survival of effective components in the blood.
- Shaking auto stops when bags are taken away during collection and restart working after bags are remounted.
- If collection volume is preset, the balance will stop shaking when there is 10ml gap and get into accurate measuring status.
- Automatic alarm when reaching the preset value.
- Humanization design and reasonable structure is convenient for operation.



Technical Parameters:

Model	LM-CM-12A	LM-CM-12B
Measuring Range	0-1200ml	
Measuring Accuracy	2%	
Display Accuracy	1ml	
Liquid Proportion	1.05g/ml	
Collection Speed	0.5~3ml/s	
Swing Frequency	30-32 r/min	
Swing Angle	13±2°	
Alarm	Audio and visual alarm	Audio and visual alarm with interrupter
Interrupter Thrust	/	<14N
Consumption	12W	40W
Power Supply	AC110/220V±10%» 50/60HZ	
External Size(W*D*H)	218*172*160mm	275*230*210mm
Packing Size(W*D*H)	310*260*210mm	330*280*260mm
Net/Gross Weight	2.8kg/3.5kg	4.2kg/5.5kg

